



HEAVY DUTY DOOR CLOSER



Commercial Grade 1 surface closer that conforms to the ANSI A156.4 standards and is UL/UL10C Listed. The adjustable (4016BC) closers meet the Americans with Disabilities Act requirements of 5 lbs. Interior and 8.5 lbs. exterior, ANSI A117.

PRODUCT FEATURES

- Installation types; regular, top jamb & parallel arm mount.
- Two independent non-critical valves for sweep and latch to provide consistent closing speeds.
- Adjustable hydraulic backcheck standard to provide cushioning and prevents uncontrolled opening of the door.
- Spring power adjustable sizes: 1-6 standard for interior and exterior applications.
- Meets the ADA requirements of 5lbs. interior and 8.5 lbs. exterior for ANSI A117.
- Cast iron body and cast steel arm.
- SNB standard.
- Backcheck positioning valve standard.
- Non-handed.
- Maximum opening of up to 180 degrees.
- Fasteners compatible for aluminum, hollow metal and wood doors and frames.
- Full high impact plastic cover standard.
- Retrofits LCN 4041.
- 25 year limited warranty to be free of manufacturer's defects.
- A wide variety of options are available (see accessories page).



HEAVY DUTY DOOR CLOSER

ACCESSORIES

PARALLEL ARM DROP PLATE

For use in mounting closer in parallel arm applications.



DP18PA

TOP JAMB DROP PLATE

For use in mounting closer in top jamb applications.



DP-18TJ

FRICTION HOLD OPEN

Standard friction hold open arm (non-handed).



HO4000

HOLD OPEN CUSH ARM


Cushion dead stop hold open arm. Prevents door from being damaged (non-handed).



CUSHHO4000

SEX NUTS

Sex nuts for 1-3/4" thick doors



SEXNUT